


Elfin ID

High Resolution Inkjet Printer



User Manual

IMPORTANT

To ensure the best printing quality, we recommend using only our specified cartridges and the corresponding accessories. Any malfunction or poor printing quality caused by improper use of other kinds of inks or accessories will be not be guaranteed.

Safety Precautions

There is high voltage inside the machine when it is live. Maintenance or disassembly by unqualified or unauthorized person is strictly prohibited, so as not to cause any accident.


Machine must be reliably grounded by connecting the grounding wire for the machine during equipment setup. Unreliable grounding will result in machine failure that the machine cannot work normally.


Do not expose ink to direct sunlight or high temperature (35°C above). The heat of direct sunlight or high temperature will affect ink's storage life and print quality.

If you get ink spill on the eyes or skin during use, please clean your eyes or skin by clean water.

Ink leakage inside printer can result in burnout damage to the machine. Switch off the machine and unplug it from power outlet when there's ink leakage inside printer. Contact qualified service technician for test and repair.

Warning Signs

Caution: The sign “” indicates information for caution of possible damage to hardware of inkjet printer or data loss.

Attention: The sign “” indicates important notes helpful for your trouble-free operation of the machine.

Content

Introduction

06 [Chapter One: Important Precautions for Using](#)

06 1.1 Important Setup Precautions

6 1.2 Important Operation Precautions

7 [Chapter Two: Setup and Installation Instructions](#)

8 2.1 Parts List

9 2.2 Device installation

09 2.2.1 Side printing installation

9 2.2.2 Down printing installation

10 2.2.3 Springback mechanism installation (optional)

11 [Chapter Three: Device Introduction](#)

11 3.1 Controller Introduction

11 3.2 Printer head Introduction

12 3.3 Technical Specifications

13 [Chapter Four: How to Use the Printer and the Check Work before/after Use](#)

13 4.1 How to Use the Printer

13 4.2 Check Work before Use

13 4.3 Check Work after Use

14 [Chapter Five: Printer Operation Instructions](#)

14 5.1 Main Interface

15 5.2 Printing Management

15 5.2.1 Find/Preview Data

15 5.2.2 Start Printing / Printing Report

15 5.2.3 Printing Delay

16 5.2.4 Print Initial Values

16 5.2.5 Stop Printing

17	5.3 New/Edit Data
17	5.3.1 New/Edit Data
18	5.3.2 Add Text Object
18	5.3.3 Add Production Date Object
18	5.3.4 Add Expiration Date Object
19	5.3.5 Add Image Logo Object
19	5.3.6 Add Counter Object
19	5.3.7 Add Shift Code Object
20	5.3.8 Add Barcode Object
21	5.3.9 Delete Data or Object
22	5.4 System Management
22	5.4.1 System Setting
23	5.4.2 Edit Options
24	5.4.3 Printing Options
26	5.4.4 Special Features
27	5.4.5 Screen Touch Correction
28	5.5 Tools Management
28	5.5.1 Image Management
28	5.5.2 System Upgrade
29	5.5.3 System Backup
29	5.5.4 System Record
29	5.5.5 About Equipment
30	5.5.6 System Reset
31	5.6 Edit Input Method Options
32	5.7 Status Bar
33	Chapter Six: Care and Maintenance
33	6.1 Printer Care and Maintenance
33	6.2 Ink Cartridge Care and Maintenance
34	Chapter Seven: Troubleshooting
34	7.1 Troubleshooting for Ink Cartridge
35	7.2 Troubleshooting for Printer
36	Appendix 1: Terms and Definitions

Please read this manual carefully before you use this equipment.

Introduction

Thank you for your purchase of this high resolution printer. We want you to get helpful information for your work with this equipment; therefore we would like to explain a little bit about how to use this machine by this user manual by the following content:

- Important precautions for use of the machine
- Introduction of printer: Parts and components of the machine
- Setup and Installation Instructions: Instructions for Equipment Setup and Cartridge Installation.
- How to use the printer and the check work before/after use of the printer: explanations of general operation and startup/shutdown.
- Operation instructions: explanations on how to new/edit data for printing, and how to adjust printer settings.
- Care and Maintenance: Care and maintenance for printer and cartridge
- Troubleshooting: Common failures occurred and solutions
- Appendix 1 - Terms and Definitions: Definitions for terms used in this document.

Please read this user manual carefully before first use of the printer for full understanding and attention of important information so that you will get maximum use from your new equipment. This will also help you have a quick reference to related sections when you have any problems during use.

Note 1: If you cannot solve the problem encountered during use, please contact us for assistance.

Note 2: The information contained herein is subject to change without notice. The amended information will be updated in user manual by new edition.

Note 3: Any machine failure or damage caused by user's negligence in following this manual will not be covered by the warranty.

Chapter One: Important Precautions for Using

Welcome to use this printer. In order to protect your personal safety and user rights, ensure correct installation and operation, and full play of the machine, it is important that you read the precautions carefully.



1.1 Important Setup Precautions

- 1.1.1 Use exclusive power supply for the equipment. Do not share same power supply with other equipment. Besides, Installation of an additional UPS is recommended.
- 1.1.2 Mount the support in sound and stable place. Do not choose the location that will be easily affected by shock or sway.
- 1.1.3 Choose well-working conveyor belt for high print quality.
- 1.1.4 Add deflector to the printer for production line setup in order to prevent any printing object hitting the nozzle plate to cause damage.
- 1.1.5 Make sure the printer is well grounded.
- 1.1.6 Maintain the distance between deflector and printing object at 0.5-2.5mm as recommended.
- 1.1.7 Make sure to insert and remove the ink cartridge by an angle of 15 degree so as not to cause damage to the cartridge.
- 1.1.8 Make sure the setup environment is tidy and clean. Clean the dust on printer from time to time when dusty environment is unavoidable.





1.2 Important Operation Precautions

- 1.2.1 Do not poke or impact the touch screen sharply.
- 1.2.2 Do not cover up the built-in photocell. Otherwise the printer doesn't print.
- 1.2.3 Use Non-woven to wipe the nozzle plate when the print is not clear or dots are missing.
- 1.2.4 Set print delay value for best print result when print position changes (see Section 5.2.3).
- 1.2.5 Do not insert or remove ink cartridge while the machine is in printing process so as not to cause damage to the cartridge.
- 1.2.6 Do not use compressed air for cleaning the touch screen. High pressure of the compressed air will damage the touch screen.
- 1.2.7 Do not use compressed air for direct or indirect cleaning of the ink cartridge. High pressure of the compressed air will damage the nozzle plate.
- 1.2.8 Read Chapter Seven for troubleshooting when there's failure occurs. If you cannot solve the problem encountered, contact your local dealer or our after-sale service.

Note: Depending on properties, some ink cartridge may require to be removed from printer after use. Turn off the machine and remove the cartridge from printer. Wipe the printhead clean with Non-woven; cap the printhead with the designed cap for prevention of the nozzles from clogging. (Contact our after-sale service for information of ink properties.)

Chapter Two: Installation and Setup Instructions

This chapter will illustrate how to set up the equipment and how to install an ink cartridge. Firstly please check the machine parts by looking at the packing picture and parts list.


Packing Picture	
	

2.1 Parts List

Once you have unpacked your machine, check to make sure that you have all the parts shown here.



1、 Controller



2、 Printer head



3、 USB



4、 power line



5、 power supply adapter



6、 printer head
connection line



7、 ground line



8、 round bar fixer X 2



9、 round bar



10、 bi-direction bracket



11、 bi-pass clamp x 2



12、 A. M8*16 SCREW: 11PCS
B. M4*8 SCREW: 2PCS




13、 inner hexagon spanner




14、 Springback holder and
anti shock groups (selectable)

2.2 Device installation


2.2.1 Side printing installation




2.2.2 Down printing installation



2.2.3 Springback mechanism installation (optional)




Springback mechanism installation




Anti-shock plate installation

Chapter three:Device Introduction

3.1 Controller Introduction



3.2 Printer head Introduction



3.3 Technical Specifications

A. Performance Values

Item	Specifications		Note
Technical source	HP TIJ 2.5 Thermal Ink Jet technology		
Dimension	Controller(H*W*D):142*65*98mm Printer head(H*W*D): 145*80*60mm		
support size	Two steel tubes: Φ16mm*350mm, and Φ16mm*280mm.		Clamp and bracket not included
Power supply	Input: AC 90V-240V/50-60HZ, 60W;		With power adapter
	Output: 12V DC / 5A;		
	Power cord length: 1.8m; Power adapter cord length: 1.2m		
Print heights	1-12.7mm		
Print speed and resolution	horizontal resolution (DPI)	Maximum speed (m/min)	
	600	30.4	
	400	45.7	
	300	60.9	
	150	121.9	
Print application	Barcode, alphabetic, numeric, image logos, date/time, expiration date, shift code, counter, lot-box code		
Connection Ports	1.Ethernet port; 2.USB2.0 port; 3.DB15 port. 4.DB25 port.		
Interface	5inch full-color large LCD touch screen with resolution 800*480.		
Ink management	1. Automatically recognizes ink types, and identifies optimum printing parameters for each ink type; 2. Guarantees the using of genuine original HP ink; 3. Automatic measuring system for the usage of ink.		
Mounting	Standard side, downward and anti-shock support.		
Product Certification	CE, FCC.		
Environment requirement	1. Working environment: -10°C~ +55°C; 10%-85%RH; 2. Storage environment: -25°C~ +80°C; 10%-90%RH.		

B. Features:

Item	Specifications	Note
Languages	Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian.	
Font	Default font is Arial; allow users to load fonts they need.	
Barcode	UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128, PDF417, DATAMATRIX, QR.	
Date format	Variety of date formats available	
Counter	Flexible setting for common counter, lot-Box code counters.	
Print speed	Print speed can be set, automatically tested, or set and tested by external encoder.	
Built-in photocell	Good for simple print, no external photocell needed.	
Multi-management	Multi-level password protection (Operator, Technician and administrator).	










C. Ink Solutions:

1. Support 42ml, 370ml, 350ml cartridges of HP TIJ2.5 technology;
2. Support ink of various colors: black, red, green, yellow and blue;
3. Support porous, semi-porous and non-porous substrates.

Chapter Four: How to Use the Printer and the Check Work before/after Use

In this Chapter, you will learn how to use the printer, including check work before and after use.

4.1 How to Use the Printer

Sq #	Procedure	Instructions
1	cartridge Installation	Insert cartridge into the printer stall by an angle of 15 degree, close cartridge clip to secure. (see 2.3 Cartridge Installation)
2	Turn on printer	Connect power adapter to printer power input, switch on power, printer enters initialization startup. 
3	Main Interface - Printing Management	After initialization startup, "main interface" appears (see Section 5.1). Click  to enter "Printing Management" (see Section 5.2). 
4	Select data - Start printing	Select a file on data list, click  to Start printing. 
5	Printing report	When printing starts, the button change to the icon  for stop printing, meanwhile a printing report appears. 
6	Stop printing	Click  to stop printing, printing report exits, and the button returns to "Start printing" status. 
7	Switch off	Exit printing, and switch off power.

4.2 Check Work before Use

Sq #	Item	Check Work
1	Printer support	Is the support securely mounted?
2	Printer position	Is the printer orientation correct? Is the nozzle plate parallel to printing object? Is the throw distance controlled within 0.5-2.5mm?
3	cartridge	Is the cartridge wiped clean? Has the cartridge been installed to printer?
4	Power input	Is the printer input voltage normal?
5	Printer status	Check status bar, is the equipment status normal?






4.3 Check Work after Use

Sq #	Item	Check Work
1	Printer Power Status	Is the printer power switched off?
2	cartridge	Is the cartridge removed from printer and wiped clean and printhead capped?


Chapter Five: Printer Operation Instructions


This chapter explains how to operate printer interface, including Printing Management, Data Management, System Management, Tools Management, and Status Bar.

5.1 Main Interface

Switch on power, printer starts initialization startup. After initialization startup, “main interface” appears (see Figure 1).			
	Printing Management	To find and preview data, start/stop printing, set printing delay value, and set printing initial values (see Section 5.2).	
	Data Management	To Find/Preview, File-new, Edit, Delete data (see Section 5.3).	
	System Management	To manage system setting, editing options, printing options, user authority, and screen correction setting (see Section 5.4).	
	Tools Management	To manage image logo, system upgrade, system backup, system record, equipment default restoring, system resetting (see Section 5.5).	
Status bar		Display information of ink, equipment, USB, encoder, external photocell, and Ethernet status (see Section 5.7).	

5.2 Printing Management

Click  on main interface to enter printing management (see Figure 2)





(Figure 2)

5.2.1 Find/Preview Data (see Figure 2)

A. Find data	Find by Pageup/Pagedown/keywords.
B. Preview data	Preview data by locating or selecting a file of data to display on preview interface; data located/selected will be displayed in sequence on preview interface, and can be viewed scaled up and down by times of 1 and 2.
Note: Drag the scroll bar horizontally to view the data when it exceeds the screen horizontally.	


5.2.2 Start Printing / Printing Report


Click  button to start printing. When printing starts, a printing report appears (see Figure 3). Printing report: It is the timely record of printing in process, including data file name in process, print output quantity, counter value, shift code, system time. The printing report exits when printing stops.




(Figure 3)

5.2.3 Printing Delay

Click , printing delay setting interface appears (see Figure 4)





 See Appendix 1: Terms and Definitions 1 for more information.




(Figure 4)

A. Printing delay default value: 30mm;	
B. Printing delay value range: 0.0-999.9mm;	
C. It is allowed to set printing delay value during printing process: the newly set value becomes valid for immediately next printing.	
D. Printing delay value for each message are independent from one another, the delay setting for current data file will not affect another data file.	


5.2.4 Print Initial Values


<p>Click  Initial, the interface of initial values setting and repeated index value checking appears.</p> <p>System switch DEC-10 decimal (0-9) H36-36 hexadecimal (0-Z) The Generic Binary is editable; See5.4.2</p>	 <p>The dialog box titled 'Initial value setting' contains a 'Current value' field with '1' and a 'Repeat index' field. Below these are 'Counter 1' and a '1' in a box. To the right are up and down arrow buttons. At the bottom are 'OK' and 'Cancel' buttons. A 'System switch' icon (three horizontal lines) is on the left, and a 'DEC' button is next to it. Red dashed arrows point from the 'System switch' and 'Counter synchronizing' labels to the 'System switch' icon and the 'DEC' button respectively.</p>
<p>Counter Synchronizing: when multi counter included in the same file, click , then all counters' current value will be synchronized to counter 1's current value.</p> <p>After confirmed, a dialog box will display the counters' setting, user can set the counter's begin/end/step/repeat number and the binary regulation.</p>	 <p>The top dialog box is identical to the one in the first row. The bottom dialog box is also identical, showing the 'Initial value setting' interface with the same fields and buttons.</p>


5.2.5 Stop Printing

<p>Click  Stop to stop printing and exit printing report, return to Start Printing status (see Figure 2).</p>	
<p>Note: Printer automatically stops printing when there is case as power-off, out of ink, alarming etc.</p>	

5.3 New/Edit Data



Click  on main interface to enter data management interface .





New

Modify

Delete

Delete All

5.3.1 New/Edit Data

Click  or  on Data Management interface to enter data edit interface (see Figure 7).

A. New: text, counter, shift, production date, expiration date, image logo, barcode.

B. Edit: data in printing process cannot be edited.

C. File name: maximum 15 characters, empty file name or repeated file name not allowed.




Image Logo

Expiration date

Production date

Text

Shift code

File name



barcod


e


Counter

Add objects

Delete objects

 Click  to save data when finish editing, a check box appears to ask “Are you sure you want to save the message? Cancel, Yes, No” (see Figure8).








If you click “”, the machine will remain on editing interface.







(Figure 8)

Note: “MSG001” is default data in system, not editable and not erasable.
The system allows maximum 500 files of data (including default MSG001).
The system does not save empty data.





5.3.2 Add Text Object

<p>Click  to add text object, see Figure 9.</p> <p>Click  to enter text editing interface:</p> <p>A. Font: default font Arial, support 2 fonts at same time, Arial and one alternative font.</p> <p>B. 16-208(adjust freely within the scope of 1-12.7mm);</p> <p>C. Text horizontal scale: 1-300%;</p> <p>D. Text content cannot exceed 25 characters.</p>	 <p>(Figure 9)</p>
<p>Click  to enter text adjustment interface.</p> <p>E. Coordinate location: adjustable range for X axis 0-3000mm; for Y axis, 0-12.7mm.</p> <p>F. Text orientation: 0°, 90°, 180°, 270°.</p> <p>Four orientations adjustable.</p> <p>G. Font effects: bold, italic, underline, strikethrough, four effects adjustable.</p>	 <p>(Figure 10)</p>
<p> Note: Please refer to this Section (Section 5.3.2) regarding how to add objects as “production date”, “expiration date”, “image Logo”, “counter”, “shift code”, “dynamical text”, “dynamical logo”, but the content of “production date”, “expiration date”, “counter”, “shift code”, “dynamical text”, “dynamical logo” cannot be revised or adjusted directly when you add, and the font, height, content and font effect of “image Logo”, “dynamical logo” cannot be revised directly. There is no option of horizontal scale “” for “logo”, “barcode”, “dynamical logo”.</p>	


5.3.3 Add Production Date

<p>Click  to add object “production date”.</p> <p>Click  to enter date format setting, choose a format by arrow up and down  Gregorian and Hijri available. (see Figure 11).</p>	 <p>(Figure 11)</p>
---	---

5.3.4 Add Expiration Date

<p>Click  to add object of expiration date.</p> <p>Click  to enter date format setting and days to expire (scope: 0~9999)  Gregorian and Hijri available. (see Figure 12).</p>	 <p>(Figure 12)</p>
---	---

5.3.5 Add Image Logo

Click  to add object image Logo.

Select a logo on file list by page up and down (see Figure 13).





Image file list
(Figure 13)


Note: When there is no image file found, a message box appears to prompt image import (see Figure 14).


See Section 5.5.1 Image Management for image logo import.





(Figure 14)

5.3.6 Add Counter



Click  to add object counter.

Click  to for option of common counter, box number, lot number.


A. Click  for common counter setting: minimum value, maximum value, stepping value, repetition number.



Common counter
Box No.
Lot No.
Stepping value
Repetition number

B. Click  and  option of box number and lot number setting: minimum value, maximum value, stepping value for box number and lot number (see Figure 16).


Note: There is no repetition number for box number or lot number.




Minimum value
Maximum value

(Figure 16)

5.3.7 Add Shift Code


Click  to add object "shift code".

Click  to enter setting (see Figure 17).

Shift code: shift name and time for setting.













Shift name: maximum five characters.

Shift time: four different times for setting. Shift code varies according to different time periods.










(Figure 17)


5.3.8 Add Barcode


<p>Click  to add object "barcode".</p> <p>A. Click  to enter barcode edit: Barcode type, horizontal scale level, barcode height, barcode text (see Figure 18).</p>	 <p>(Figure 18)</p>
<p>B. Click  to enter barcode adjustment: coordinate location, text orientation, text display/hide, text height, error correction level, white space level (see Figure 19, 20).</p> <p>Note: Setting options may differ depending on different barcode types.</p> <p> Text: Text display;</p> <p> Text: Text hide;</p> <p> ~  : error correction level;</p> <p> ~  : white space level.</p>	 <p>(Figure 19)</p>  <p>(Figure 20)</p>

5.3.9 Delete Data or Object


<p>Select an object on data editing interface,</p> <p>click  Delete to delete the object, a dialog box appears to prompt if you are sure that you want to delete.</p>	
<p> In the data management interface name list box to choose this information,</p> <p>click  Delete the delete ,delete the data,</p> <p>click  DeleteAll delete all,delete all data.</p> <p>Note: message in printing cannot be deleted.</p>	 


5.4 System Management


Click  to enter system management (See Figure 26).














5.4.1 System Setting

Click  on system management interface to enter system setting (see Figure 27).




A. System language	Standard language in delivery country as default language.
B. System time	Manufacture time as default time, can be set by user.
C. Screen saver time	<p> see Appendix 1: Terms and Definition 3.</p> <p>1) System default 5 minutes, 4 options for changeover: 5minutes, 3 minutes, 1minute, OFF.</p> <p>2) If screen saver is optioned OFF, screen enters standby status if inactive for 1hour.</p> <p>3) Screen becomes active when there's alarm or error.</p>
D. unit	Switch between mm and inch. language in delivery country as default language.
E. Daylight saving time	Three modes for setting: OFF, European summer time, US summer time.
F. Calendar Type	two modes available: Gregorian and Hijri. Default setting is Gregorian; System time will be changed according to the calendar setting.


5.4.2 Edit Options

<p>Click  on system management interface to enter edit options setting interface.</p>	
<p>A. Click  to enter production date and expiration date format setting. Note: six common date formats default, forty-four more formats addable for user. The six default date formats not editable and cannot be deleted.</p>	
<p>Click  or  in date format setting interface, new or edit date format, date format edit interface appears.</p>	
<ol style="list-style-type: none"> 1. YYYY Year, options are: YYYY ---4-digit, --YY ---last 2 digit, __Y ---last 1 digit 2. MM Month, options are: 1-12 ---digit, 1-9-En ---Jan to Sep is 1-9, and then O/N/D, M ---abbreviations, Alt M ---full English 3. HH Hour, options are: 24H --24 hours system, 12H ---12 hours system 	
<p>B. Click  to enter special time setting.  see Appendix 1: Terms and Definitions 4, 5.</p>	
<ol style="list-style-type: none"> 1) Date transition time setting: system default normal zero o'clock as date transition time to next date, users can set different time as date transition time. 2) Pre-zero in date/time: four options: OFF, empty preposition, empty postposition, centered without zero. (e.g. 2012/05/09, 2012/_5/_2, 2012/5_/_2_, 2012/5/2). 	
<p>C. Click  to enter counter setting.</p>	
<ol style="list-style-type: none"> 1) Production counter: setting extent: 0~99999999. 2) Pre-zeros: four options: OFF, empty preposition, empty postposition, centered without zero (e.g. 0001, __1, 1__, 1). 3) Counter alarm: ON or OFF option. When counter alarm is turned ON, the machine will stop printing, sound alarm and prompt message that print number reaches maximum value. 4) Counter reset: ON or OFF option. All counters will start from initial values if the counter reset is turned ON. The printing value will continue with the last one if the counter reset is turned OFF. 	



5.4.3 Printing Options

Click  on system management interface to enter printing option setting.

A. Click  to enter nozzle maintenance setting (see Figure 31).





(Figure 31)


Note: 1) Pre-purge Mode: 2 modes:  both right & left nozzles;  the working nozzles only.

2) Pre-purge: four shifts: OFF, low, medium, high. see the following figures:



 see Appendix 1: Terms and Definitions 6, 7.

B. Click  to enter printhead setting (see Figure 32).




(Figure 32)



3 Note: printing direction: system default from left to right.

1) Four directions optional: left-to-right, right-to-left, mirror sides of left-to-right and right-to-left, see figures as follows:




2) channel switch: Left channel, Right channel, Dual channel, see the figures as follows:




3) Printing Recovery: when the set is  , printer will resume printing automatically when the power continue. The default setting is .

Note: When the printing contains counter, and the Printing Recovery setting is "ON", operator need to check on the counter value and do needful adjustment.


 see Appendix 1: Terms and Definitions 8.







C. Click  to enter production line setting (see Figure 33).



Line speed: system default 30m/min;
Adjustable scope 1~150m/min;
DPI: system default 300DPI; adjustable
scope 50~600DPI.



(Figure 33)











Click  on line speed setting interface to run speed test (see Figure 35, 36).

Line speed test: input test object length 0~3000mm, click  to enter speed test startup interface, then start production line, the photocell will be sensing the object, and the machine will calculate line speed automatically. Click  to save current speed test result. Click , current speed test value will not be saved. If test repeated, system will take average value of multiple results. Click  to stop speed test, and click  or  to save or give up test result.





Note: if external encoder is connected, system can detect automatically, and switch line speed interface to encoder DPI setting interface. User cannot programme line speed setting when external encoder is connected.


5.4.4 Special Features

<p>Click  on system management interface to enter “Special Features” setting.</p> <p>A. Click  to enter “Special printing” setting .</p> <p>Continuous printing:</p> <p> See Appendix 1: Terms and Definitions 9 for more information.</p> <p>1) Continuous output times: system default 0 (OFF). Adjustable scope 0~9999. Note: 0 is equal to OFF; 9999 equal to infinite.</p> <p>2) Output interval: system default OFF, adjustable scope 0~999mm.</p>	 <p>The screenshot shows the 'Special' settings menu. It has two main options: 'Special' (with a printer icon) and 'Alarm' (with a bell icon). The 'Special' option is selected, showing a 'Times' field set to '0' and a 'Distance' field set to 'mm'. Red dashed arrows point from the text labels on the left to the corresponding UI elements: 'Special printing' to the 'Special' button, 'Continuous output' to the 'Times' field, and 'Output interval' to the 'Distance' field. At the bottom are 'Calibrate' and 'Return' buttons.</p>
<p>B. Click  to do Alarm settings.</p> <p>User can choose Alarm Light or Production Line Control.</p> <p>Alarm Light: operation please refer to above picture.</p> <p>Production Line Control:  Stop</p> <p>Printing;  Device Abnormal;</p> <p> Ink Empty; Ink Use-up;</p> <p> Ink Alarm;</p> <p>These options can be multi-selected.</p> <p>When the above situation happen, printer will transfer the error signal to the production line via DB15 ports, user can set the production line reaction like stop or etc.</p>	 <p>The screenshot shows the 'Alarm' settings menu. It has two main options: 'Special' (with a printer icon) and 'Alarm' (with a bell icon). The 'Alarm' option is selected, showing a 'TrnLED' field set to 'On' and a 'CtrlLine' field set to 'On'. Red dashed arrows point from the text labels on the left to the corresponding UI elements: 'Alarm' to the 'Alarm' button, 'Alarm Light' to the 'TrnLED' field, and 'P.L control' to the 'CtrlLine' field. Below this, there are two more sections. The first section has 'Stop printing' and 'Ink Use-up' options, each with a 'Stop' button. The second section has 'Device Abnormal' and 'Ink Alarm' options, each with a 'DevError' button. Red dashed arrows point from the text labels on the left to the corresponding UI elements: 'Stop printing' to the 'Stop' button, 'Ink Use-up' to the 'InkEmpty' button, 'Device Abnormal' to the 'DevError' button, and 'Ink Alarm' to the 'InkAlarm' button. At the bottom are 'Calibrate' and 'Return' buttons.</p>

5.4.5 Screen Touch Correction

<p>Click  Calibrate on system management interface to enter screen touch correction (see Figure 41).</p> <p>Note: Please correct screen touch when there's inaccurate touch phenomenon. Icon "+" appears on different location on screen guides you the screen correction. The interface exits after screen touch correction finished, and a message appears to prompt screen touch correction success or failure for your attention.</p>	 <p>(Figure 41)</p>
--	---

5.5 Tools Management

Click  on main interface to enter tools management interface (see Figure 42).





Figure 42 shows the Tools Management interface. The top bar contains icons for Tool, About printer, System record, Backup management, Upgrade management, Image Logo, and System reset. The main area has buttons for Import, Delete, DeleteAll, Prev, Next, Num: 0, Reset, and Return.

5.5.1 Image Management

Click  to enter imageLogo management interface (see Figure 43).
Image import: import image from USB or Ethernet.
Image format: Solid color BMP;
Image height: 0-150 pixel point.
Image length: 0-1000000 pixel point.





Figure 43 shows the Image Logo management interface. The top bar contains icons for Tool, Image Logo, System record, Backup management, Upgrade management, Image Logo, and System reset. The main area has buttons for Import, Delete, DeleteAll, Prev, Next, Num: 0, Reset, and Return.

Note: 1) System prompts and cuts the excess part if the imported image exceeds borders.
2) Image import cannot be executed when pixel points exceed 100.
3) Image Logo document route: USB Disk/InkJet/Logo.

5.5.2 System Upgrade

Click  to enter upgrade management interface (see Figure 44).
Users can upgrade the software, add or change languages and fonts by USB.









Figure 44 shows the System Upgrade interface. The top bar contains icons for Tool, System Upgrade, System record, Backup management, Upgrade management, Image Logo, and System reset. The main area has buttons for Software, Language, Font, Execute, Prev, Next, Num: 0, Reset, and Return.



A. Software upgrade	System automatically searches for software upgrade documents in designated folder and displays the upgrade documents by list. User can select anyone in the list for upgrade. Document route: USB Disk/InkJet/Upgrade/Application.
B. Language upgrade	System is loaded with multiple languages upon delivery. User can add one more language if needed. Document route: USB Disk/InkJet/Upgrade/Language.
C. Font upgrade	System supports two fonts; user can add another font besides the default Arial. Document route: USB Disk/InkJet/Upgrade/Font.

Note: Software upgrade documents, language documents, font documents can only be identified when they are packed by the conversion tools provided by our company. The language documents, font documents are not replaceable and cannot be deleted.



5.5.3 System Backup

<p>Click  , enter the management interface</p> <p>Click  enter the operation interface output backups, can backup messages image and parameter setting</p>	
<p>click  , enter recover interface, can recover the messages, images, and parameters updated to device from USB, can choose:</p> <p>new message: data from USB to device</p> <p>replace message : replace the data</p> <p>delete message : delete the data in device</p> <p>image: as message.</p> <p>parameters: replace</p>	
<p>Note: Please check USB connection status and disk space is normal when execute backup import and export. Backup document route: USB Disk/InkJet/Backup.</p>	



5.5.4 System Record


<p>Click  to enter system record viewing interface. All operation activities including operator, operation and operation time will be shown.</p>	
<p>System record information includes:</p>	<ol style="list-style-type: none"> 1) The printing activities: printing start and stop, initial values. The printing activities: initial values setting diary. 3) All operation activities in system management (including touch screen correction). 4) Image import and delete activities, system upgrade, backup, and reset activities.
<p>Note: System record does not include querying and viewing activities.</p>	


5.5.5 About Equipment

<p>Click  to enter equipment information viewing interface.</p> <p>Information displays current hardware version, software version, machine serial number, dealer code, company Logo, company name and website.</p>	
--	--


5.5.6 System Reset

 Click  on tools management interface to enter system reset management (see Figure 48).

Click  to execute system reset. You need to enter administrator password for permission to reset execution (see Figure 49).



(Figure 48)



(Figure 49)






Note: System reset is to restore all defaults.

- 1) Restore all the settings to defaults, clear all data and images.
- 2) Maintain software version in current version; restore language and font to default.

















After system reset, system parameters are as follows:

Item #	Item	Parameter
1	Language	English
2	System time	Manufacture time
3	Screen saver time	5 minutes
4	Unit	Metric/mm
5	Daylight saving time	OFF
6	Customer year	OFF
7	Date transition time setting	OFF
8	Pre-zero in date/time	OFF
9	Pre-zero in counter	OFF
10	Counter alarm	OFF
11	Counter reset	OFF
12	Pre-purge	OFF
13	Clean printhead	Standby
14	Printing direction	Left-to-right
15	Channel switch	Left channel
16	Print Recovery	OFF
17	Line speed	30m/min
18	DPI	300DPI
19	User permission management	OFF
20	Continuous output times	0 OFF
21	Data management	Only system default data Msg001
22	Printing delay	30mm
23	Printing initial value	Counter initial value and data source current value.

5.6 Edit Input Method Options

A keypad appears when user clicks the editing bar. Keypad of Uppercase, lowercase, numeric, or common symbols for changeover (see Figure 50, 51, 52, 53).	
A. Uppercase: uppercase keypad is pre-set keypad to appear (see Figure 50).	<div></div> <div>(Figure 50)</div>
B. Lowercase: click <div>Shift</div> to change between uppercase and lowercase (see Figure 51).	<div></div> <div>(Figure 51)</div>
C. Numeric and common symbols: Click <div>?!123</div> to change between numeric or common symbols input (see Figure 52).	<div></div> <div>(Figure 52)</div>
D. More symbols: click <div>Shift</div> on numeric/common symbols keypad for more symbols (see Figure 53).	<div></div> <div>(Figure 53)</div>
<div>Shift</div>	Input changeover key
<div>?!123</div> <div>ABC</div>	Numeric/common symbols and alphabetic input changeover key.
<div>Clean</div>	Remove key (clear all input)
<div>←</div>	Delete (delete one character)
<div></div>	Hide keypad

5.7 Status Bar (See Figure 1)

	Ink information	<p>Ink information includes dynamic and static information. Static information includes cartridge serial number, client code, cartridge type. Dynamic information: 1) ink original volume, and prospect print output for current data. 2) Ink remaining percentage, prospect print output for current data.</p> <p>Ink status icons include:</p> <p>1) Normal (): Normal ink status.</p> <p>2) warning (): ink amount lower than 10%;</p> <p>3) Error (): wrong cartridge, cartridge not installed, or ink used up.</p>	
	Equipment status	<p>Hardware and software status in printer. (e.g. Printing not started)</p>	
	USB information	<p>Automatically displays by icon for equipment normally connected to USB port. Support three devices: USB disk, mouse, and keyboard. Status: not connected (gray), normal connection (green), warning (yellow).</p> <p>Normally connected equipment will be displayed by icon  USB disk,  mouse, or  keyboard.</p>	
	Encoder information	<p>Displays encoder or photocell connection status as unconnected (gray) and normally connected (green).</p>	<p>When encoder is connected, click  , encoder signal test interface appears.</p> 
	Photocell information	<p>Displays encoder or photocell connection status as unconnected (gray) and normally connected (green).</p>	<p>When photocell is connected, click  , photocell signal test interface appears.</p> 

Chapter Six: Care and Maintenance

Printer is a precision machine. To keep your machine work properly and bring facilitation to your production; to keep your machine in good condition and extend equipment life, it is important to carry out proper care and maintenance on machine from time to time.

6.1 Printer Care and Maintenance

- 6.1.1 Make sure power cord, power adapter cord, grounding wire is in good condition. Make sure the contact of each cord or wire is reliable.
- 6.1.2 Make sure the screw for grounding wire is secured and the grounding is reliable.
- 6.1.3 Make sure the equipment is not displaced. Make sure the nozzle plate is parallel to printing object, and printing distance is controlled within 0.5-2.5mm. (Please use the designed tools provided by our company to secure the mounting support).
- 6.1.4 Clean ink cartridge: wipe nozzle plate with Non-woven to keep nozzles clean and unclogged. (Please refer to ink cartridge care and maintenance for instructions).
- 6.1.5 Keep touch screen clean. Do not hit touch screen sharply.
- 6.1.6 Keep machine surface and ports clean.
- 6.1.7 Check status bar, make sure equipment icon is normal and there's no alarming status on status bar. (In case of alarm status, check troubleshooting for solution)
- 6.1.8 When machine is turned off, make sure to remove the cartridge from printer, clean the nozzle plate and cap the printhead, and place the cartridge in safe environment. (Please refer to cartridge care and maintenance for instructions).

6.2 Ink Cartridge Care and Maintenance

Maintain correct methods for use and storage of the cartridge will keep the cartridge work with best print quality and extend cartridge life. Please always follow instructions in Ink Cartridge Care and Maintenance. The warranty will not cover damage or failure caused by negligence in following our care and maintenance instructions.

- 6.2.1 Ink volatilizes slowly if the cartridge is decapped. Keep new and undecapped cartridge in its original package. Decap new cartridge only when it is to be used.
- 6.2.2 Try to use up ink as soon as possible once the cartridge is decapped to prevent blockage because ink become dry on nozzle plate very soon.
Note: Due to property difference, different inks have different dry time and care and maintenance methods. Contact our after-sale service for more information.
- 6.2.3 If ink in cartridge is not used up at a time after decapped, remove the cartridge from printer and cap the printhead and store it in airtight container provided by our company. (Storage temperature is room temperature).
Note: Do not use adhesive tape to seal the printhead, and do not store cartridge in soft plastic bag.
- 6.2.4 Nozzle plate is delicate. Do not touch or clean nozzle plate with anything sharp or rough so as not to scratch nozzle plate.
- 6.2.5 Use the Non-woven provided by our company to wipe and clean nozzle plate.
Note: Wipe nozzle plate with the printhead facing down. Move the printhead in the direction of nozzle channel. Move the printhead in the direction across nozzle channel will damage the nozzles.
- 6.2.6 Do not shake ink cartridge or expose it to vibration. Shake or vibration will get air run into cartridge and affect print quality.

To ensure best print quality, contact our company's after-sale service for information of instructions for different inks.

Chapter Seven: Troubleshooting



Note 1: The table below lists the most commonly seen problems and the solutions to each. If there's any other problem, contact your local dealer or our after-sale service for assistance.

Note 2: The table below is for reference only because causes for each problem may differ depending on individual situation such as setup environment, operation demand.

7.1 Troubleshooting for Ink Cartridge

Sr.#	Problem	Problem	Solutions	Comments
1	The print has broken line or white line.	1. Nozzle blockage or damage.	A. See Section 6.2 Ink Cartridge Care and Maintenance, wipe and clean nozzle plate with Non-woven; B. See Section 5.4.3, purge the nozzles by the option "Clean Printhead".	If the problem is still unsolved: Check if there's any spring-loaded connectors depressed in Driver board; Check if there's contamination on cartridge contact plate.
		2. Cartridge not in good contact with printer.	Remove the cartridge and re-insert.	
2	The print is complete at first, and then becomes incomplete	Ink starvation or air bubbles blocking nozzles.	A. Check status bar if there's alarm of low ink. B. Send back to our company for test.	
3	The print is totally blank.	Ink used up or total nozzle blockage.	See Section 5.7 to check ink status: is ink used up?	
4	Unable to identify ink cartridge.	1. Connectivity problem on printer (defect or damage)	Remove cartridge and re-insert.	If problem is unsolved: Check if there's any spring-loaded connectors depressed in driver board. Check if there's contamination on cartridge. Check if there's contamination on ISM card. Check if there's any connector depressed on ISM card board.
		2. Cartridge dealer code mistake.	Remove cartridge and re-insert.	

7.2 Troubleshooting for Printer

Sr.#	Problem	Cause	Solutions	Comment
1	Printer cannot be switched on	1.No power input;	A. Make sure AC power input on adapter is correct, DC output on adapter is well connected with printer. B. Check if power adapter light is normal. Replace a new adapter if light is dead, dim or blinking.	
		2. Printer switch not turned on.	Make sure the printer power switch is turned ON.	
		3. Equipment damage.	Contact local dealer or after-sale service.	
2	Printer does not print	1. Printing not started.	Click “Start printing” button to start printing.	
		2. No data for printing.	Select a file and click “Start printing” button.	
		3. Printing delay value too big.	Check if the printing delay value is normal.	
		4. Cartridge not installed.	Install a cartridge.	
		5. Cartridge installed but used up or damaged.	Check cartridge status according to Section 5.7, is ink used up or cartridge dealer code wrong?	If ink used up, or cartridge dealer code wrong, replace a new cartridge.
		6. Photocell not works.	Cover up the photocell to check according to 5.2.2 to see if there's variation in print output quantity in printing report.	When the external equipment is photocell, click  for photocell signal test interface, test if photocell works.
		7. Encoder is connected but damaged.	Check if the encoder and its connection wire are in good condition; check if the production line is running well.	When the external equipment is encoder, click  for encoder signal test interface, move encoder to check if the encoder works.

Appendix 1: Terms and Definitions

Sr.#	Term	Definition	Comment
1	Printing delay	It is the distance from the point when photocell senses the printing object to the point when printing starts. User can adjust the value to alter the print position on printing object.	E.g. Printing delay value is 30mm, printer starts printing at 30mm point after the photocell senses the printing object.
2	Printing initial value	It is beginning value in printing process for print data.	E.g. Set the initial value as 9, the counter counting starts from 9 for first print.
3	Screen saver time	It is a power saving function, the screen will automatically turn off and enter standby mode when the screen is inactive for a time period as set.	E.g. Set the screen saver time as one minute. The screen will automatically turn off and enter standby mode if the screen becomes inactive for one minute.
4	Customer year	It is the special year on customer demand. Customer can change the year in date format by any round number within scope.	E.g. The system date is 2012/07/31. Supposed the date by customer is 2010/07/31, customer can set the year in date as 2010. Then the date shown on the print will be 2010/07/31.
5	Date transition time setting	When system time reaches certain point, the printout date and time will be that of the next date.	For example: Current date is 07.10, set the date transition time to be 07:59, then the time of last printing out before that is recorded as 09/07 07:59, after that is 10/07, 8:00. If the date transition time is 12:01, then the time of last printing out before that is recorded as 10/07 12:00, after that is 11/07.
6	Pre-purge	Ink becomes dry on nozzle plate during use. The dried ink will make the print not clear for half of first character. To prevent this phenomenon, user can turn this function ON.	When Pre-purge function is turned ON, printer will spray a little ink at optioned level during idle period in printing process to keep nozzle plate warm and moist so as to eliminate dried ink phenomenon.
7	Clean Printhead	Customer can use this function to purge nozzles.	Purge whole nozzle plate, make sure nozzles are unblocked.
8	Channel switch	Customer can switch for different channel to achieve best print quality according to print need and nozzle channel condition.	E.g. At option of single-channel printing, when there are damage in left channel nozzle or there are missing dots in print by left channel, user can switch to right channel printing. At option of dual-channel printing, left channel and right channel will work at same time for printing to achieve darker print and best print quality.
9	Continuous printing	Multiple outputs of same print during one session of period photocell sensing the print object.	
10	Printing Recovery	When there is a power failure, and the setting is "ON", system will go back to the last printing status and resume printing when power gets back. The default setting for this function is "OFF"	When the printing contains counter, and the Printing Recovery setting is "ON", operator need to check on the counter value and do needful adjustment.



Sojet Electronics(Xiamen) Co.,Ltd.

Add: Room 402 4/F, Hong Ye Building,Chuang Ye Park,

Torch Hi-Tech Industrial Development Zone, XiaMen, Fujian, China

Tel: +86-592-5771357 Fax: +86-592-5565048

E-mail: partner@sojet-tech.com

Website: www.sojet-tech.com

Zip code: 361006